



TECHNIQUES

TECHNOLOGIE HYBRID	
MOTEUR	Giant SyncDrive Sport, 70Nm, powered by Yamaha, PedalPlus 6-sensor technology
ECRAN	Giant RideControl Dash, Smart Assist automatic mode, 5 support levels, USB-C (10W)
COMMANDE	Giant RideControl Dash, high-angle visibility, full color LCD display
BATTERIE	Giant EnergyPak 500Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 250 range extender compatible
CADRE	
TAILLES	S, M, L, XL
COLORIS	Amber Glow
CADRE	ALUXX aluminum, Overdrive 1½ - 1⅝" head tube, 141mm Boost QR, ISS, EnergyPak Plus Range Extender compatible, integrated KSA18 kickstand mount
FOURCHE	SR Suntour XCM32 NLO DS 15AH2, 27.5 [XS-S] / 29 [M-L], 120mm travel, tapered steerer, lockout
AMORTISSEUR	n/a
COMPOSANTS	
CINTRE	Connect TR Riser 31.8x690mm [XS-S], 750mm [M-L]
POIGNÉES	Tactal single lock-on
POTENCE	Contact 31.8 alloy
TIGE DE SELLE	Forge alluminum 30.9mm 2-bolt micro adjustable
SELLE	Liv Sport
PÉDALES	Aluminum Platform
DÉRAILLEUR	
MANETTES	microSHIFT ADVENT e-optimized
DÉRAILLEUR AVANT	n/a
DÉRAILLEUR ARRIÈRE	microSHIFT ADVENT, 9-speed
FREINS	Tektro HD-M285, hydraulic disc, 180mm
LEVIER DE FREIN	Tektro HD-M285
CASSETTE	microSHIFT ADVENT, 11-42T, 9-speed, e-optimized
CHAÎNE	KMC e.9 Sport, e-bike optimized
PÉDALIER	FSA MegaTooth direct-mount 1X steel 36T alloy crank arm
BOITIER DE PÉDALIER	n/a

ROUES	
JANTES	XCT 27.5 [XS-S] / 29 [M-L] Tubeless Ready 25mm e-bike optimized
MOYEUX	Shimano MT400 Boost, Center-Lock, 110x15 [XS-S] / Shimano HB-TC500-15 100x15 [M-L] [F], MT200-B 141mm OLD, QR [R]
RAYONS	Stainless steel
PNEUS	Maxxis Rekon 27.5x2.4" [XS-S] / 29x2.4" [M-L], Wire Bead 60TPI
EXTRAS	-
ACCESSOIRES	
ECLAIRAGE	-
ANTI-VOL	-
PORTE-BAGAGES	-

Prix Public Conseillé: 3 000,00 €

GÉOMÉTRIE

CADRE	XS	S	M	L
Longueur de tube de selle (mm)	365	405	445	485
Angle de tube de selle	74,0°	73,5°	73,0°	73,0°
Longueur du tube supérieur (mm)	560	565	595	615
Longueur du tube de direction (mm)	110	115	105	115
Angle du tube de direction	68,0°	68,0°	68,0°	68,0°
Déport de fourche (mm)	42	42	46	46
Trail (mm)	103,8	103,8	99,5	99,5
Empattement (mm)	1130	1130	1161	1182
Longueur des bases (mm)	475	475	475	475
Hauteur du boîtier de pédalier (mm)	50	50	45	45
Stack (mm)	621	626	625	634
Reach (mm)	382	380	404	421
Hauteur en statique (mm)	680	710	750	755
Largeur de cintre (mm)	690	690	750	750
Longueur de potence (mm)	40	50	50	60
Longueur des manivelles (mm)	165	165	170	170
Diamètre des roues	[F] 27.5+"	[F] 27.5+"	[F] 29" [R]	[F] 29" [R]

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.