

# TRANCE X E+ 2



## TECHNIQUES

| TECHNOLOGIE HYBRID  |                                                                                                                                                                                                                                         |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MOTEUR              | SyncDrive Pro 2, 85Nm, powered by Yamaha                                                                                                                                                                                                |
| ECRAN               | Giant RideControl Ergo3, grip integrated remote                                                                                                                                                                                         |
| COMMANDE            | Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display                                                                                                                                                       |
| BATTERIE            | Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible                                                |
| CHARGEUR            | Giant EnergyPak 6A smart charger, 60% in 2:15h                                                                                                                                                                                          |
| CONNECTIVITY        | Giant RideControl App enabled ANT+ wireless display signal with e-bike profile                                                                                                                                                          |
| CADRE               |                                                                                                                                                                                                                                         |
| TAILLES             | S, M, L, XL                                                                                                                                                                                                                             |
| COLORIS             | Messier / Black                                                                                                                                                                                                                         |
| CADRE               | ALUXX SL-grade Aluminum, Advanced Forged Composite linkage, 140mm Maestro Suspension System, 'Boost' 148x12 UDH rear axle, Giant EnergyPak Plus Range Extender Compatible                                                               |
| FOURCHE             | Fox 36 Float Rhythm E-Tuned, 29er, 150mm travel, 44mm offset, Grip Damper, Sweep adjust, Boost 110x15QR                                                                                                                                 |
| AMORTISSEUR         | Fox Float DPS Performance, EVOL Large Volume sleeve, 3-position Lever, 185x52.5mm Trunnion mount, custom tuned, recommended sag: 30%                                                                                                    |
| COMPOSANTS          |                                                                                                                                                                                                                                         |
| CINTRE              | Giant Contact 35 Trail, 35x780mm                                                                                                                                                                                                        |
| POIGNÉES            | Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)                                                                                                                                                          |
| POTENCE             | Giant Contact SL 35                                                                                                                                                                                                                     |
| TIGE DE SELLE       | OBC Giant Contact Switch AT Travel adjustable 172D-CONTAC-0053 total length 315 T100-70MM / 172D-CONTAC-0052 total length 395 T140-110MM / 172D-CONTAC-0051 total length 470 T170 -140MM / 172D-CONTAC-0050 total length 530 T200-170MM |
| SELLE               | Giant Romero E                                                                                                                                                                                                                          |
| PÉDALES             | Flat pedal                                                                                                                                                                                                                              |
| DÉRAILLEUR          |                                                                                                                                                                                                                                         |
| MANETTES            | Shimano SLX                                                                                                                                                                                                                             |
| DÉRAILLEUR AVANT    | MRP HD2 co-moulded chain guide                                                                                                                                                                                                          |
| DÉRAILLEUR ARRIÈRE  | Shimano SLX, 12-speed, Shadow+                                                                                                                                                                                                          |
| FREINS              | Shimano Deore, BR-M6120, 4-piston, hydraulic disc, 203mm                                                                                                                                                                                |
| LEVIER DE FREIN     | Shimano Deore, I-spec EV                                                                                                                                                                                                                |
| CASSETTE            | Shimano CS-M6100-12, 10-51T, 12-speed                                                                                                                                                                                                   |
| CHAÎNE              | KMC e.12 Turbo, EcoProteq, e-bike optimized                                                                                                                                                                                             |
| PÉDALIER            | Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (Q-factor=168, S:160, M/L:165, XL:170)                                                                                                      |
| BOITIER DE PÉDALIER | n/a                                                                                                                                                                                                                                     |

| ROUES                    |                                                                                                                                         |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| JANTES                   | Giant AM30, Tubeless ready, 30mm inner width, 29"                                                                                       |
| MOYEUX                   | Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle                                             |
| RAYONS                   | Sapim E-Lite [R] Race [F], e-bike optimized                                                                                             |
| PNEUS                    | Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra [F]Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+, 3C MaxxTerra [R] |
| EXTRAS                   | Tubeless kit (liquid, valves, levers, manual, tool)                                                                                     |
| ACCESSOIRES              |                                                                                                                                         |
| ECLAIRAGE                | Kit d'éclairage avant et arrière à piles                                                                                                |
| ANTI-VOL                 | Torx 25 Battery Lock with built-in Torque limiter                                                                                       |
| LIMITES                  |                                                                                                                                         |
| POIDS TOTAL MAX AUTORISÉ | 156 kg (vélo, cycliste et bagages)                                                                                                      |

Prix Public Conseillé: 5 300,00 €

## GÉOMÉTRIE

| CADRE                              | S             |  | M             |  | L             |  | XL            |  |
|------------------------------------|---------------|--|---------------|--|---------------|--|---------------|--|
|                                    | LOW   HIGH    |  | LOW   HIGH    |  | LOW   HIGH    |  | LOW   HIGH    |  |
| Longueur de tube de selle (mm)     | 400           |  | 425           |  | 450           |  | 475           |  |
| Angle de tube de selle             | 76,0°   76,7° |  | 76,0°   76,7° |  | 76,0°   76,7° |  | 76,0°   76,7° |  |
| Longueur du tube supérieur (mm)    | 577   575     |  | 610   605     |  | 637   635     |  | 667   665     |  |
| Longueur du tube de direction (mm) | 95            |  | 100           |  | 110           |  | 120           |  |
| Angle du tube de direction         | 65,7°   66,5° |  | 65,8°   66,5° |  | 65,8°   66,5° |  | 65,8°   66,5° |  |
| Déport de fourche (mm)             | 44            |  | 44            |  | 44            |  | 44            |  |
| Trail (mm)                         | 117   122,4   |  | 117   122,4   |  | 117   122,4   |  | 117   122,4   |  |
| Empattement (mm)                   | 1205   1206   |  | 1239   1237   |  | 1268   1269   |  | 1300   1301   |  |
| Longueur des bases (mm)            | 473   473     |  | 473   473     |  | 473   473     |  | 473   473     |  |
| Drop du boîtier de pédalier (mm)   | 30   20       |  | 30   20       |  | 30   20       |  | 30   20       |  |
| Stack (mm)                         | 606   601     |  | 611   605     |  | 621   614     |  | 630   624     |  |
| Reach (mm)                         | 439   447     |  | 457   462     |  | 482   489     |  | 510   517     |  |
| Hauteur en statique (mm)           | 783   789     |  | 775   784     |  | 763   770     |  | 775   782     |  |
| Largeur de cintre (mm)             | 780           |  | 780           |  | 780           |  | 780           |  |
| Longueur de potence (mm)           | 40            |  | 50            |  | 50            |  | 60            |  |
| Longueur des manivelles (mm)       | 160           |  | 165           |  | 165           |  | 170           |  |
| Diamètre des roues                 | 29"           |  | 29"           |  | 29"           |  | 29"           |  |

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.