

# TRANCE X ADVANCED E+ ELITE 3



## TECHNIQUES

TECHNOLOGIE HYBRID	
MOTEUR	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
ECRAN	Giant RideControl Ergo3, grip integrated remote
COMMANDE	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
BATTERIE	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGEUR	Giant EnergyPak 4A smart charger, 60% in 1:45
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CADRE	
TAILLES	S, M, L, XL
COLORIS	Messier/Panther
CADRE	Advanced-grade composite frame, AluXX SL-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system
FOURCHE	RockShox 35 Gold RL DebonAir, 150mm travel, 44mm offset, MotionControl™ rebound and lockout control, 15x110 Boost, Maxle Stealth, e-MTB optimised
AMORTISSEUR	Rock Shox Deluxe Select R, DebonAir, 185x52.5mm Trunnion mount, custom tuned
COMPOSANTS	
CINTRE	Giant Contact SL 35 Trail, 35x780mm
POIGNÉES	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
POTENCE	Giant Contact SL 35
TIGE DE SELLE	Tranz-X Rad+ dropper, 30,9mm, 30mm travel adjustable (S:120-150mm, M:140-170mm, L/XL:170-200mm)
SELLE	Giant Romero, Neutral
PÉDALES	n/a
DÉRAILLEUR	
MANETTES	Shimano Deore
DÉRAILLEUR AVANT	MRP HD2 co-moulded chain guide
DÉRAILLEUR ARRIÈRE	Shimano Deore 12-speed, Shadow+
FREINS	Shimano BR-MT420, 4-piston, hydraulic disc, 203mm [F/R]
LEVIERS DE FREIN	Shimano Deore, I-spec EV
CASSETTE	Shimano CS-M6100-12, 10-51T, 12-speed
CHAÎNE	KMC e.12 Turbo, EcoProteq, e-bike optimized
PÉDALIER	Praxis N.W. 36T Cold Forged 4130 premium steel Praxis e-Cranks (Q-factor=168, S:160, M/L:165, XL:170)
BOITIER DE PÉDALIER	n/a

ROUES	
JANTES	Giant AM30, Tubeless ready, 30mm inner width, 29" [F] / 27.5" [R]
MOYEURS	Shimano MT410 Boost, Center-Lock, 110x15 [F] 148x12 Shimano Micro-Spline Drive Body Thru-axle [R]
RAYONS	Sapim E-Lite [R] Race [F], e-bike optimized
PNEUS	Maxxis Minion DHF 29x2.50" Foldable, TLR, EXO [F] Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool) Inner tube supplied
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles
LIMITES	
POIDS TOTAL MAX AUTORISÉ	156 kg (vélo, cycliste et bagages)

Prix Public Conseillé: 6 500,00 €

## GÉOMÉTRIE

CADRE	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longueur de tube de selle (mm)	400	425	450	475				
Angle de tube de selle	77,2°   78,0°	76,0°   76,7°	76,0°   76,7°	76,0°   76,7°	76,0°   76,7°	76,0°   76,7°		
Longueur du tube supérieur (mm)	577   575	607   605	636   634	665   663				
Longueur du tube de direction (mm)	95	100	115	130				
Angle du tube de direction	65,7°   66,5°	65,8°   66,5°	65,8°   66,5°	65,8°   66,5°	65,8°   66,5°	65,8°   66,5°		
Déport de fourche (mm)	44	44	44	44				
Trail (mm)	113,1   108	113,1   108	113,1   108	113,1   108				
Empattement (mm)	1194   1195	1215   1212	1244   1244	1275   1275				
Longueur des bases (mm)	447   447	447   447	447   447	447   447				
Drop du boîtier de pédalier (mm)	10	10	10	10				
Stack (mm)	607   601	611   605	625   619	639   633				
Reach (mm)	439   447	457   462	480   487	505   513				
Hauteur en statique (mm)	726   735	733   742	732   741	741   750				
Largeur de cintre (mm)	780	780	780	780				
Longueur de potence (mm)	40	40	50	50				
Longueur des manivelles (mm)	160	165	165	170				
Diamètre des roues	R27.5" / F	R27.5" / F	R27.5" / F	R27.5" / F				

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.